

PRODUCT DESCRIPTION



CCA06006025

ENCLOSURE WITH BLIND DOOR, 1 DOOR

*representative image

TECHNICAL CHARACTERISTICS

PRODUCT CODE	CCA06006025	
DESCRIPTION	ENCLOSURE WITH BLIND DOOR, 1 DOOR W600 X H600 X D250	
MATERIAL	STAINLESS STEEL AISI 304 (1.4301)	
MATERIAL FINISHING	SCOTCH BRITE	
IP PROTECTION GRADE EN 60529	IP66	
IK RATING EN 62262	IK10	
NEMA RATING 250	4X	
UL/CSA UL508A CERTIFICATION, CSA C22.2 n° 14-13	NEMA 1.12.4.4X	
DIMENSIONS	WIDTH mm	600
	HEIGHT mm	600
	DEPTH mm	250
BODY	THICKNESS mm	1.2
	SINGLE-BODY CONSTRUCTION BENT AND CONTINUOUSLY WELDED	
DOOR	THICKNESS mm	1.2
	AIS I 304 STAINLESS STEEL CONCEALED HINGES, DOOR OPENING GREATER THAN 120° POLYURETHANE GASKET (RANGE TEMPERATURE: -40°C + 90°C)	
NUMBER OF DOORS	1	
NUMBER OF HINGES	2	
NUMBER OF LOCKS	2	
LOCK	CHROMED ZAMAK 3MM DOUBLE BIT LOCK	
NUMBER OF REAR FIXING	4	
FIXING INSERT	BLIND THREADED M6	
REAR FIXING DISTANCE	WIDTH mm	510
	HEIGHT mm	540
SUPPLY KIT	INTERNAL PLATE FIXING SCREWS KIT AND DOUBLE FIN KEY	
	GROUNDING SCREW KIT	
PACKAGING	CARDBOARD	
WEIGHT (PLATE EXCLUDED)	Kg	20.5
VOLUME	m ²	0.09

(OPTIONAL) INTERNAL PLATE	PLATE CODE	CPE060060
	MATERIAL	GALVANIZED STEEL
	WIDTH mm	547
	HEIGHT mm	570
	ENCUMBRANCE mm	14
	THICKNESS mm	2.5
	WEIGHT Kg	9.05

POWER DISSIPATION TABLES

POWER DISSIPATION



MAXIMUM DISSIPABLE POWER IN WATT (W) FOR ALLOWED OVERTEMPERATURE (T °) VALUES (EXTERNAL TEMP. + OVERTEMPERATURE = 60 ° C)

			REAR RAGAINST WALL			
W	H	D	OVERTEMPERATURE VALUES (dT)			
			25 °C	30 °C	35 °C	40 °C
mm	mm	mm	W	W	W	W
600	600	250	118	141	164	188

POWER DISSIPATION



MAXIMUM DISSIPABLE POWER IN WATT (W) FOR ALLOWED OVERTEMPERATURE (T °) VALUES (EXTERNAL TEMP. + OVERTEMPERATURE = 60 ° C)

			ALL SIDES FREE			
W	H	D	OVERTEMPERATURE VALUES (dT)			
			25 °C	30 °C	35 °C	40 °C
mm	mm	mm	W	W	W	W
600	600	250	94	112	131	150

download link CAD drawing: <https://www.compex.it/download/>