

PRODUCT DESCRIPTION



CCA12008030

ENCLOSURE WITH BLIND DOOR, 2 DOORS

*representative image

TECHNICAL CHARACTERISTICS

PRODUCT CODE	CCA12008030	
DESCRIPTION	ENCLOSURE WITH BLIND DOOR, 2 DOORS W1200 X H800 X D300	
MATERIAL	STAINLESS STEEL AISI 304 (1.4301)	
MATERIAL FINISHING	SCOTCH BRITE	
IP PROTECTION GRADE EN 60529	IP55	
IK RATING EN 62262	IK10	
NEMA RATING 250	1.12	
UL/CSA UL508A CERTIFICATION, CSA C22.2 n° 14-13	NEMA 1.12	
DIMENSIONS	WIDTH mm	1200
	HEIGHT mm	800
	DEPTH mm	300
BODY	THICKNESS mm	1.5
	SINGLE-BODY CONSTRUCTION BENT AND CONTINUOUSLY WELDED	
DOOR	THICKNESS mm	1.5
	AIS I 304 STAINLESS STEEL CONCEALED HINGES, DOOR OPENING GREATER THAN 120° POLYURETHANE GASKET (RANGE TEMPERATURE: -40°C + 90°C)	
NUMBER OF DOORS	2	
NUMBER OF HINGES	4	
NUMBER OF LOCKS	4	
LOCK	CHROMED ZAMAK 3MM DOUBLE BIT LOCK	
NUMBER OF REAR FIXING	6	
FIXING INSERT	BLIND THREADED M6	
REAR FIXING DISTANCE	WIDTH mm	1110
	HEIGHT mm	740
SUPPLY KIT	INTERNAL PLATE FIXING SCREWS KIT AND DOUBLE FIN KEY	
	GROUNDING SCREW KIT	
PACKAGING	CARDBOARD	
WEIGHT (PLATE EXCLUDED)	Kg	54.7
VOLUME	m ²	0.29

(OPTIONAL) INTERNAL PLATE	PLATE CODE	CPE120080
	MATERIAL	GALVANIZED STEEL
	WIDTH mm	1147
	HEIGHT mm	770
	ENCUMBRANCE mm	14
	THICKNESS mm	2.5
	WEIGHT Kg	24.24.00

POWER DISSIPATION TABLES

POWER DISSIPATION



MAXIMUM DISSIPABLE POWER IN WATT (W) FOR ALLOWED OVERTEMPERATURE (T °) VALUES (EXTERNAL TEMP. + OVERTEMPERATURE = 60 ° C)

			REAR RAGAINST WALL			
W	H	D	OVERTEMPERATURE VALUES (dT)			
			25 °C	30 °C	35 °C	40 °C
mm	mm	mm	W	W	W	W
1200	800	300	282	339	395	451

POWER DISSIPATION



MAXIMUM DISSIPABLE POWER IN WATT (W) FOR ALLOWED OVERTEMPERATURE (T °) VALUES (EXTERNAL TEMP. + OVERTEMPERATURE = 60 ° C)

			ALL SIDES FREE			
W	H	D	OVERTEMPERATURE VALUES (dT)			
			25 °C	30 °C	35 °C	40 °C
mm	mm	mm	W	W	W	W
1200	800	300	218	261	305	348

download link CAD drawing: <https://www.compex.it/download/>